

CARRIAGE OF SOLID BULK CARGOES CERTIFICATE OF COMPLIANCE

Issued in accordance with the provisions of the
International Maritime Solid Bulk Cargoes (IMSBC) Code,
As adopted by Resolution MSC. 268(85), as amended

Issued

By INTERNATIONAL REGISTER OF SHIPPING

Under the authority of the Government of REPUBLIC OF PALAU

Certificate Number: 18-03-026 G3/SBC

PARTICULARS OF SHIP

Name of Ship: IVANKA

Distinctive Number or Letters: T8A2606

Port of Registry: MALAKAL HARBOR

Gross Tonnage: 3145

IMO Number: 8004129

Ship Type: GENERAL CARGO

Date on which keel was laid . 01 JANUARY 1980

THIS IS TO CERTIFY:

That the ship is suitable for the carriage in bulk of all cargoes in cargo holds, as listed in the supplement of this certificate, in accordance with the provisions of the International Maritime Solid Bulk Cargoes (IMSBC) Code, subject to the following:

- 1) The relevant construction and equipment are maintained in good order
- II) The cargo being loaded and carried in accordance with the approved "Loading Manual" provided on board
- III) The cargo being loaded and carried in accordance with the approved "Trim and Stability Manual" provided on board
- IV) The applicable "Special Requirements" for the carriage of each cargo being complied with, as per the IMSBC Code, (see cargo list attached)
- V) The Master being responsible for the remaining requirements of the IMSBC Code, being complied with as applicable.

This certificate will remain valid until 27 AUGUST 2018

Issued at ISTANBUL - TURKEY on 28 MARCH 2018

PROVISIONAL - Validity not to exceed five months

<u>Mostafa Ismael</u>
Surveyor to International Register of Shipping

R0029728

It is agreed that International Register of Shipping (hereafter referred as the society), its subsidiaries, bodies, officers, directors, employees and agents shall have no liability for any loss, damage or expense allegedly caused directly or indirectly by their mistake or negligence, breach of warranty, or any other act, omission or error by them including gross negligence or Willful misconduct by any such person with the exception of gross negligence or Willful misconduct by the governing bodies or senior executive officers of the society. If any person used the services of the Society or its subsidiaries or relies on any decision made or information given by or on behalf of them and in consequence suffers a loss, damage or expense proved to be due to their negligence, omission or default, then the Society will pay by way of compensation to such person a sum limited to the value of fees paid to the Society. Under no circumstances whatsoever shall the individual or individuals who have personally caused the loss, damage or expense is held liable.

SUPPLEMENT TO THE CERTIFICATE OF COMPLIANCE

LIST OF CARGOES PERMITTED TO BE CARRIED*				
CARGO	Group	UN No.	IMO CLASS	Cargo Space
ALL CARGOES OF GROUP A AND GROUP C	A & C	-		Hold no.1 & no.2
COAL ^{1, 4, 5, 6, and 7)}	B (and A)	2000-12	МНВ	Hold no.1 & no.2
COAL SLURRY ⁴⁾	A	-		Hold no.1 & no.2
AMMONIUM NITRATE BASED FERTILIZER (NON-HAZARDOUS) ^{1, 2, and 3)}	С	-		Hold no.1 & no.2
CHOPPED RUBBER AND PLASTIC INSULATION	С	<u>-</u>		Hold no.1 & no.2
COARSE CHOPPED TYRES ⁴⁾	С	-		Hold no.1 & no.2
GRANULATED TYRE RUBBER	С	<u>-</u>		Hold no.1 & no.2
SULPHUR (FORMED, SOLID) ⁵⁾	С	-		Hold no.1 & no.2

Note*: i) Vessel may carry all cargoes categorized in Group A of the Code except Coal Slurry, unless specified in above list.

ii) Vessel may carry all cargoes categorized in Group C of the Code except 1) Ammonium Nitrate Based Fertilizer (non-hazardous); 2) Chopped Rubber and Plastic Insulation; 3) Coarse Chopped Tyres; 4) Granulated Tyre Rubber; 5) Sulphur (formed, solid), unless specified in above list.

iii) For cargoes categorized in Group B of the Code, only those specified in above list can be carried.

LIST OF FOOTNOTES

- 1. Electrical Equipment in the cargo holds are to be isolated from the electrical supply and to be secured against unintentional reconnection
- 2. Stowage at least 03 m distance from machinery space bulkhead, e.g. with a grain bulkhead or other means of separation
- 3. Not to be stowed adjacent to tanks, double bottoms or pipes containing fuel oil heated to more than 50°C.
- 4. A suitable detector for quantitative measurements of methane is to be provided
- 5. A suitable detector for quantitative measurements of oxygen (0-21% by volume) is to be provided
- 6. A suitable detector for quantitative measurements of carbon monoxide is to be provided
- 7. Not to be stowed adjacent to tanks, double bottoms or pipes containing fuel oil heated to more than 55°C. The fuel oil temperature is to be controlled at less than 55°C. This temperature shall not exceed for periods greater than 12 hours in any 24 hour period and the maximum temperature reached shall not exceed 65°C

Mostafa Ismae No. 1464

Surveyor to International Register of Shipping